

MS.e

Metering dosing pumps

Constant flow rate regulation.
PVDF pump head with FPM seals



- LCD 2.1/2 digit display
- Flow rate digital adjustment 0-100% by keys
- PVDF pump head as standard
- Power on led
- Led Alarm
- Solenoid pulse Led
- Chemical dosing alarm level on demand
- ON/OFF switch
- Start/Stop key
- Polypropylene Plastic box with 30% fiber glass
- IP65 protection degree

SELECTION GUIDE

MODEL	FLOW RATE MAX (l/h)	PRESSURE MAX (bar)	FREQUENCY MAX (imp/min)	ML/PULSE	MAX SUCTION HIGH (m)	STANDARD POWER SUPPLY (*)	WEIGHT (kg)
MS.E 01-15	1	15	120	0,14	2.0	230 V-50/60 Hz	1,4
MS.E 02-10	2	10	120	0,28	2.0	230 V-50/60 Hz	1,4
MS.E 05-05	5	5	120	0,69	2.0	230 V-50/60 Hz	1,4

(*) For other power supply consult factory.

MATERIALS OF CONSTRUCTION

PARTS	MATERIALS
Pump head	PVDF (on request: Polypropylene)
Diaphragm	PTFE
Connections	PVDF
Foot filter	Polypropylene
Injection valve	Polypropylene
Suction tube	PVC crystal 4x6 mm.
Delivery tube	Polyethylene 4x6 mm.
Standard valves	Ceramic ball
Seals	FPM (on request: EPDM)
On request	Level connection (BNC)
Max current	1A

OVERALL DIMENSIONS

